



郑州高德机械设备有限公司
Gaode Equipment Co., Ltd.

地址 ADD : 郑州市金水区丰庆路 4 号院 14 号楼 9 号

邮编 P.C.:450053

No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China

网站 (Web) :www.gaodetec.com

E-Mail: info@gaodetec.com

电话 TEL.:+86-371-55951660

Automatic Membrane Filter Press

Introduce:

Membrane filter press adopts international advanced TPE membrane technology so that it ensures stable performance and long life-span, and widely used for various industries.

Cake from membrane filter press can be secondly squeezed under max 1.6Mpa by water to realize the lowest cake residual moisture. In some wastewater treatment industries, the final cake can be used for landfill or burning directly.



Features:

- The use of low pressure filtration and high pressure can greatly shorten the entire filtration cycle.
- The material is TPE elastomer, the feeding pressure can reach 1.6MPa, and the pressing pressure can reach 2.0MPa.

Email: info@gaodetec.com



郑州高德机械设备有限公司

Gaode Equipment Co., Ltd.

地址 ADD : 郑州市金水区丰庆路 4 号院 14 号楼 9 号

邮编 P.C.:450053

No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China

网站 (Web) :www.gaodetec.com

E-Mail: info@gaodetec.com

电话 TEL.:+86-371-55951660

- The moisture content is greatly reduced, saving subsequent costs.
- Squeeze can choose air, inert gas, water, oil and other fluid media to meet the needs of different industries.
- The structure is made of high-quality carbon steel Q345b and processed with sandblasting to remove rust and getting higher intensity and corrosion resistance.

Apply

This membrane filter press is widely used in sewage treatment, various concentrates and tailings, metallurgy, chemical, pharmaceutical, food, ceramics and other industries and fields. Especially for viscous materials, it has a unique filtering effect, such as municipal wastewater, printing and dyeing wastewater, fine chemicals, etc





GAODETEC

郑州高德机械设备有限公司 Gaode Equipment Co., Ltd.

地址 ADD : 郑州市金水区丰庆路 4 号院 14 号楼 9 号

邮编 P.C.:450053

No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China

网站 (Web) :www.gaodetec.com

E-Mail: info@gaodetec.com

电话 TEL.:+86-371-55951660

Filter plate:



Filter cloth:



Email: info@gaodetec.com



GAODETEC

郑州高德机械设备有限公司

Gaode Equipment Co., Ltd.

地址 ADD: 郑州市金水区丰庆路4号院14号楼9号

邮编 P.C.:450053

No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China

网站 (Web) :www.gaodetec.com

E-Mail: info@gaodetec.com

电话 TEL.:+86-371-55951660

Factory



Email: info@gaodetec.com



郑州高德机械设备有限公司 Gaode Equipment Co., Ltd.

地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053
No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China
网站 (Web): www.gaodetec.com E-Mail: info@gaodetec.com
电话 TEL.: +86-371-55951660

Technical parameters:

规格型号 Model	过滤面积(m²)	滤板尺寸(mm)	滤室厚度(mm)	滤室容积(L)	滤板数量(pcs)	过滤压力(Mpa)	电机功率(Kw)	整机质量(Kg)	外形尺寸长×宽×高(mm)	地基尺寸(mm) Foundation Size(mm)			
	Filter area	Plate size	Cake thickness	Filter chamber volume	Plate NO.	Filtration pressure	Motor Power	Weight	Dimensions L×W×H(mm)	L	B	D	H
X _M G30/870-U _K ^B	30	870×870	≤35	498	23	≥0.8	2.2	3046	3880×1350×1230	2920	700	1270	785
X _M G40/870-U _K ^B	40			623	29			3593	4270×1350×1230	3300			
X _M G50/870-U _K ^B	50			789	37			4057	4790×1350×1230	3820			
X _M G60/870-U _K ^B	60			955	45			4597	5310×1350×1230	4340			
X _M G70/870-U _K ^B	70			1121	53			5136	5830×1350×1230	4860			
X _M G80/870-U _K ^B	80			1287	61			5636	6350×1350×1230	5380			
X _M G50/1000-U _K ^B	50	1000×1000		776	27		4	4352	4270×1500×1360	3350	780	1400	870
X _M G60/1000-U _K ^B	60			943	33			4480	4770×1500×1360	3780			
X _M G70/1000-U _K ^B	70			1109	39			5263	5130×1500×1360	4210			
X _M G80/1000-U _K ^B	80			1275	45			5719	5560×1500×1360	4640			
X _M G100/1000-U _K ^B	100			1608	57			6555	6410×1500×1360	5490			
X _M G120/1000-U _K ^B	120			1941	69			7466	7260×1500×1360	6340			

Email: info@gaodetec.com



GAODETEC

郑州高德机械设备有限公司 Gaode Equipment Co., Ltd.

地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号

邮编 P.C.:450053

No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China

网站 (Web) :www.gaodetec.com

E-Mail: info@gaodetec.com

电话TEL.:+86-371-55951660

规格型号 Model	过滤面积(m²)	滤板尺寸(mm)	滤室厚度(mm)	滤室容积(L)	滤板数量(pcs)	过滤压力(Mpa)	电机功率(Kw)	整机质量(Kg)	外形尺寸长×宽×高(mm)	地基尺寸(mm)			
	Filter area	Plate size	Cake thickness	Filter chamber volume	Number plate	Filtration pressure	Motor Power	Weight	Dimensions L×W×H(mm)	L	B	D	H
X _M ^A G80/1250-U _K ^B	80	1250×1250	≤40	1560	29	≥0.8	5.5	10900	4830×1800×1600	3960	850	1740	995
X _M ^A G100/1250-U _K ^B	100			1975	37			11750	5440×1800×1600	4570			
X _M ^A G120/1250-U _K ^B	120			2391	45			12600	6060×1800×1600	5180			
X _M ^A G150/1250-U _K ^B	150			2911	55			13620	6820×1800×1600	5950			
X _M ^A G160/1250-U _K ^B	160			3119	59			14470	7130×1800×1600	6255			
X _M ^A G200/1250-U _K ^B	200			3847	73			15320	8200×1800×1600	7325			
X _M ^A G240/1250-U _K ^B	240			4679	89			16170	9420×1800×1600	8550			
X _M ^A G250/1250-U _K ^B	250			4783	91			17020	9570×1800×1600	8700			
X _M ^A G200/1500-U _K ^B	200	1500×1500		3809	49		11	26120	7140×2200×1820	5870	1170	1990	1070
X _M ^A G250/1500-U _K ^B	250			4723	61			26930	7730×2200×1820	6860			
X _M ^A G300/1500-U _K ^B	300			5637	73			28160	8720×2200×1820	7850			
X _M ^A G350/1500-U _K ^B	350			6551	85			29600	10110×2200×1820	9090			
X _M ^A G400/1500-U _K ^B	400			7618	99			31500	11260×2200×1820	10240			
X _M ^A G450/1500-U _K ^B	450			8532	111			33400	12250×2200×1820	11230			
X _M ^A G500/1500-U _K ^B	500			9446	123			33380	13240×2200×1820	12220			
X _M ^A G600/2000-U _K ^B	600	2000×2000		11901	85		15	54164	13030×3000×2500	10610	1660	2000	1050
X _M ^A G700/2000-U _K ^B	700			13838	99			58300	14390×3000×2500	11920			
X _M ^A G800/2000-U _K ^B	800			14945	107			62460	15770×3000×2500	13240			
X _M ^A G900/2000-U _K ^B	900			17713	127			66620	17150×3000×2500	14560			
X _M ^A G1000/2000-U _K ^B	1000			19651	141			70780	18530×3000×2500	15880			

双击可显示空白