

地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053 No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China 回社 (Web): www.geodetec.com 电话 TEL.:+86-371-55951210 传真 FAX:+86-371-55951210

GF5 for manual CLC blocks production line

CLC is cellular light weight concrete, has been used in over 40 countries over the past year for build houses, apartments, schools, hospitals, industrial buildings etc.

Benefits of CLC blocks

1. **Lightweight**: Dry bulk density 300 kg/m^3 -1500kg/m^3 , 1/8-1/2 as light as common concrete.

2. **High Compression Strength**: compressive strength ranging from 0.6 MPa to 25 MPa, 4 times as traditional aerated concrete.

3. **Thermal Insulation**: good heat preservation and good thermal insulation.

4. **Impermeability**: Low water-intake rate and high impermeability.

5. **saving cost**: Easy and fast production. No primary energy and reduced transportation costs



Main machines for making CLC blocks include: GM1000 foam concrete mixer, GH50 foam concrete pump, Foam generator.

<image>

GM1000 foam concrete mixer



地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053 No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China 回述 (Web): www.goodotoc.com E Mail: info@goodotoc.com 电话 TEL.:+86-371-55951210 传真 FAX:+86-371-55951210

The foam concrete mixer mainly includes **mixer**, **feeder hopper**, **Foam generator**, **water pump**, **control panel**, **tank**.

Features:

1. It could mixing variable materials, such as cement, fly ash, sand pulp, sand stone, perlite, and slag etc.

Specially mixing blades, mixing the material toughly, storage in its bottom is less than 10mm, no material left on the four walls internal the mixing drum.
Variable speed mixing and internal

structure alteration make its installation easy and mixing frequency high, it saves energy.

ModelGM1000Max.Output5 m3/hMaterial input volume1000LMixing speed6-
8min/batchMixer motor power1.5kwMax. Particle Size of Aggregat
es8 mm

Main technical data sheet:

GH50 foam concrete pump



第州高德机械设备有限公司 Gaode Equipment Co., Ltd.

地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053 No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China 回述 (Web): www.goodetee.com E Mail: info@goodetee.com 电话 TEL.:+86-371-55951210 传真 FAX:+86-371-55951210

Features:

- 1. No valves
- 2. Self-priming
- 3. Only tube to replace
- 4. Spiral bevel gear SEW series

(Cycloidal pinwheel reducer gear box for option)

5. Mainly consists pump house,

rotor, idel rotor, squeeze tube, and driving unit

6. Easy maintance, low cost, short down time

Main technical data sheet:

Model	GH50
Max.Output	5 m3/h
Max.Conveying Pressure	2 MPa
Max.Horizontal Transporting Range	30 m
Max. Vertical Transporting Height	100 m
Max. Particle Size of Aggregates	10-15 mm
Motor power	7.5kw
Squeeze hose brand	Trelleborg

Note: If you need big output, please feel free to tell us.

Foam generator and foaming agent





地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053 No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China 回述 (Web): www.goodotoc.com E Mail: info@goodotoc.com 电话 TEL.:+86-371-55951210 传真 FAX:+86-371-55951210



Manual moulds



The mould size: 600x200x200mm 600x200x150mm 600x200x100mm 600x200x75mm 500x400x100mm 500x250x200mm 500x250x100mm

Also could be customized according to your demands



地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053 No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China 回述 (Web): www.geodetec.com E Mail: info@geodetec.com 电话 TEL.:+86-371-55951210 传真 FAX:+86-371-55951210

If want to improve efficiency, you could use wire cutting machine.



It is specially used to cut various foam concrete blocks. Easy operation, high efficiency. The block size between 100-200-300-400-500-600-700-800-900-1000-1100-1200mm could be adjusted willfully.

Name	GW 30B Wire Cutting Machine	
Electric Motor (Kw)	2.2 kw*1 set, 0-56r/min adjusted	
	750w*2 set, 0-560r/min adjusted	
Effective hoisting height	700mm	
Cutting plantform	1240*1240*225mm	
size (L*W*H)		
Net cutting size (L*W*H)	1200*1200*600mm	
Cutting cycle	60-180seconds	
Overall dimension (L*W*H)	2160*2060*2280mm	
Total weight	1100kg	



地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053 No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China 回社 (Meh): www.goodetee.com E Mail: info@goodetee.com 电话 TEL.:+86-371-55951210 传真 FAX:+86-371-55951210

The brick made by our GF5 concrete foam block making machine :



Note: The Foam concrete's other application

- 1. External wall thermal insulation
- 2. Thermal insulation roofing
- 3. Thermal flooring
- 4. Upstanding beam foundation ditches filling
- 5. Sound insulation and fire protection walls
- 6. Playground and track construction
- 7. Sound insulation layer, tunnel lining filling
- 8. Cellar, basement and arch filling
- 9. Sewers and Drains filling
- 10. Horizontal floor heightening
- 11. Water tank and fuel tank building
- 12. Platform filling and mending
- 13. Garden and rockeries
- 14. Foam concrete block
- 15. Foamed concrete precasting ,hollow wallboard casting





Gaode Equipment Co., Ltd. Add: No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China P.C.: 450000 Tel:+86-371-55951210/55951660/55090761/55090762 Fax: +86-371-55951210 Email: info@gaodetec.com lena@gaodetec.com caroline@gaodetec.com

Web: www.gaodetec.com