



GMP50/40 Mortar Spraying Machine

Brief introduction:

GMP50/40 Mortar Spraying Machine is a kind of piston and ball controlling pump, and the conveying line, piston and cylinder is specially designed and processed, so this machine is workable for high-pressure grouting/spraying mortar (the mixture of sand: cement: water). And it is successfully used in sealing, strengthening, stabilizing of rock and soil, tunneling, building hydro-power project, etc, and also used for spraying mortar in construction and 3D Panel, etc.

Feature:

Single piston with single-acting.

Ball valve

Mechanical transmission

Integrate pump head and hopper

Prevent eduction and deposition together with the paddle agitating

Technical data:

Rated Output	50L/min
Rated Pressure	4MPa(40bar/580PSI)
Cylinder Dia.	90mm

Piston Stroke	85mm
Stroke/Minute	95/min
Inlet diameter	75mm
Outlet diameter	50mm
Max. Aggregate size	5mm
Water cement ratio	1: 3
Power unit	5.5KW(Electric)
10hp(Diesel)Chassis	Skid or Tyre
Weight	450kg
Overall Dimensions	1715x1024x900(mm)

A complete set of GMP50/40 mortar pump

No	Description	Qty.	Unit
1	GMP50/40 MORTAR PUMP	1	set
2	Nozzle Set	1	set
3	Nozzle	1	pcs
4	ID38 conveying hose,Length 10m	2	pcs
5	ID90 Rubber piston	2	pcs
6	Seal parts kit	1	set

Certificate:

CE AND ISO




Picture:

Electric motor





Diesel engine type:**The link of video:**

http://www.youtube.com/watch?v=_Yay_2K5w9c

Gaode Equipment Co., Ltd.

Add: No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China

P.C.: 450000

Tel: +86-371-55951210

Fax: +86-371-63526676

Email: info@gaodetec.com

Web: www.gaodetec.com